

NITROGEN OXIDES (NO-NO₂)

What is NO_x? Where, when and how is it formed? What are its dangers? Are NO₂ emissions regulated? How can we get rid of it? What is the warning threshold for NO pollution? Here are some answers.

What is NO_x?

NO_x sometimes refers to nitric oxide (NO), a colorless gas, sometimes refers to nitrogen dioxide (NO₂), a red gas. Nitric oxide (NO) is only ephemeral, it instantly converts to nitrogen dioxide (NO₂) in contact with the air.

NO₂ is the chemical symbol of the nitrogen dioxide molecule. This molecule consists of a nitrogen atom (chemical symbol N) and two oxygen atoms (chemical symbol O).

What are the dangers of NO₂ ?

There are at least four strong reasons to consider NO₂ as a powerful pollutant:

- NO₂ is an irritating toxic gas and a powerful suffocator that presents a real danger for living beings.

- NO₂ is a greenhouse gas with a warming power per unit mass much higher than that of carbon dioxide (CO₂).

- NO₂ is a precursor of ozone (O₃), itself a powerful irritant which is formed spontaneously in the air in the presence of NO-NO₂ by mutation of atmospheric oxygen (O₂).

- NO₂ is not biodegradable; once in the atmosphere and by mixing with water vapor, it can turn into nitric acid (HNO₃) at the origin of acid rain that dissolves vegetation, stone and concrete.

What is the NO₂ pollution threshold?

Air quality in large cities has become a constant concern. In Ile-de-France (the 1st region of France with 11 million inhabitants) this quality is constantly monitored by about fifty sensors, including ten in Paris intramural.

These sensors measure the concentration in air of major pollutants such as nitrogen dioxide (NO₂), ozone (O₃), sulfur dioxide (SO₂) and particulate matter (PM).

There are two levels of nitrogen dioxide pollution: the threshold of vigilance which is based on a concentration of 200 micrograms (2×10^{-7} kg) of NO_2 per cubic meter of air, the alert threshold being set at 400 micrograms (4×10^{-7} kg) of NO_2 per cubic meter of air.

The threshold of vigilance corresponds to the presence of a single gram of NO_2 in a volume equivalent to that of a building of 5 stages!

The threshold of vigilance results in a systematic 20 km/h reduction in speed limits applicable outside built-up areas.

The nitrogen dioxide alert results in a 30 km/h reduction in speed limits applicable outside built-up areas, but traffic restrictions or outright bans can be imposed in case of persistent pollution.

What is the pollution threshold for ozone?

There are two levels of ozone pollution: the threshold of vigilance which is based on a concentration of 180 micrograms (1.8×10^{-7} kg) of O_3 per cubic meter of air, the alert threshold being set at 360 micrograms (3.6×10^{-7} kg) of O_3 per cubic meter of air.

Given the correlation between nitric oxide (NO) emissions and the ozone pollution, the ozone warning threshold is usually reached first.

Ozone pollution result in the same measures as those for nitrogen dioxide.

How is NO- NO_2 formed by automobile engines?

The transport sector is responsible for more than half of total NO- NO_2 emissions to the atmosphere. Indeed, it is formed during the combustion of any fuel under conditions of high pressure and high temperature, by reaction of the components of the air that are oxygen (O_2) and nitrogen (N_2).

The quantities emitted are very variable, they depend on many factors: the driving style of course, but especially the type of vehicle, its engine, its fuel, the traffic conditions and atmospheric conditions.

It is assumed that diesel engines emit on average 4 times more nitric oxide or nitrogen dioxide than gasoline engines of the same category, because of the large volume of air introduced into the cylinders at the intake (supercharging) and the strong compression rate inherent in this type of engine.

It has also been found that, whatever the engines, these discharges increase significantly in urban traffic, especially in traffic jams, and more particularly in periods of high heat or strong sunshine.

About NO₂ regulations

The first anti-pollution regulations enacted in France date from 1972 and only concerned the carbon monoxide (CO) emissions measured at stop. Since then, the anti-pollution standards evolve regularly according to the requirements of the environment and the technological progress of the engines, they now apply to all the European countries (norms EURO).

Contrary to the American legislation which does not take into account the motorization, the EURO standard for cars makes a distinction between gasoline and diesel fuel, particularly with regard to emissions of NO₂:

passenger cars	EURO IV (2005)	EURO V (2009)	EURO VI (2014)
gasoline	0.06 g/km	0.06 g/km	0.06 g/km
diesel	0.25 g/km	0.18 g/km	0.08 g/km

© association adilca all rights reserved

The EURO standard for industrial vehicles takes into account the energy produced, so as not to penalize large trucks:

industrial vehicles (trucks, bus...)	EURO IV (2005)	EURO V (2009)	EURO VI (2014)
	3.5 g/kWh	2 g/kWh	0.4 g/kWh

© association adilca all rights reserved

How to interpret this standard? A modern truck^(*) traveling at a constant speed of 90 km/h (55 mph) on a horizontal road must develop a power of about 115 kW and therefore produce an energy of about 115 kWh^(**) to travel 90 kilometers (55 miles).

Under these conditions, the maximum permissible emission of 2.55 grams of NO₂ per kilometer was reduced to 0.51 grams of NO₂ per kilometer in 2014, that is still enough to pollute a volume equivalent to that of a 5 storey building in less than 2 kilometers and in less than 2 minutes. But this is the allowable limit, we hope that the best will do better ...

How can we get rid of NO₂?

Since NO₂ is not biodegradable, the source must be removed or, where this is not possible, work to reduce it, in the chemical sense of the term.

There are currently only two technologies capable of reducing the quantities of nitrogen oxides emitted by the engines:

- the EGR valve (*Exhaust Gas Recirculation*), a primitive technique that consists in reintroducing the exhaust gases to the intake in order to reduce the nitrogen dioxide by the combustion of an excess of fuel. This process is based on the affinities between the oxygen of the pollutant (O₂ of the molecule NO₂) and the hydrogen of the fuel (H of the

molecule HC). The reaction produces carbon dioxide (CO₂), water vapor (H₂O), nitrogen gas which is a non-toxic gas (N₂) and carbon (C) as particles.

- the SCR (*Selective Catalyst Reduction*) technology, currently the most successful technique of reducing the nitrogen dioxide present in the exhaust gas, through a chemical reaction in a catalyst. This process is based on the affinities between the oxygen of the pollutant (O₂ of the molecule NO₂) and the hydrogen of the additive (H₃ of the molecule NH₃). The catalyst has the function of lowering the energy threshold required for the reaction.

In addition to its significantly higher manufacturing cost, this technology has the disadvantage of having to operate with an ammonia-based additive (NH₃) stored in an independent tank. For the sake of convenience and safety, this additive is not pure ammonia but a dilute preparation based on urea [(NH₂)₂CO] marketed under the name AdBlue[®] in Europe, under the acronym DEF (*Diesel Exhaust Fluid*) in the United States.

The additive is injected directly into the exhaust line, upstream of the catalyst. The reaction reduces nitrogen dioxide (NO₂) to carbon dioxide (CO₂), gaseous nitrogen (N₂) and water vapor (H₂O) which are harmless^(***). To treat 1 gram of nitrogen dioxide requires 1.3 grams of pure additive. The reaction produces about 1 gram of carbon dioxide (CO₂), 0.9 gram of nitrogen gas (N₂) and 0.8 gram of water vapor (H₂O).

To produce carbon dioxide to get rid of nitrogen dioxide, is that not contradictory? The dangerousness of nitrogen dioxide being proven, it means above all that between two evils, it is better to choose the least. Diesel enthusiasts will have to do it: with the lowering of the imposed thresholds, SCR technology, a time reserved for trucks, has become essential since 2014 for all new cars destined for the European market.

(*) *Characteristics of the truck: frontal surface 10 m²; drag coefficient 0.9; chassis mounted on 12 wheels and tires each supporting an average load of 3.3 tons and generating a rolling resistance of 25 N / t.*

(**) *The kilowattheure (symbol kWh) is an energy unit: 1 kWh = 3.6 MJ.*

(***) *Carbon dioxide is not toxic, but it is a greenhouse gas (see ADILCA file "Carbon Dioxide"). Nitrogen gas, also known as nitrogen (to distinguish it from the nitrogen element), is the major component of ambient air (76% by mass).*

ASSOCIATION ADILCA

www.adilca.com


* * *

SOME CHEMICAL REACTIONS

Atoms molar mass (g.mol⁻¹):


hydrogen (H): 1
carbon (C): 12
nitrogen (N): 14
oxygen (O): 16

Nitric oxide formation:



N₂: nitrogen
O₂: oxygen
NO : nitric oxide

Nitric dioxide formation:



NO: nitric oxide
O₂: oxygen
NO₂: nitrogen dioxide

Ozone formation:




O₂: oxygen
O₃: ozone

Reduction of nitrogen dioxide by excess fuel:




NO₂: nitrogen dioxide
C_{7.25}H₁₃: diesel fuel
CO₂: carbon dioxide
H₂O: water
N₂: nitrogen
C: carbon

By referring to the molar mass of each element of this reaction, one obtains the following proportions:



Reduction of nitrogen dioxide by ammonia:



NO₂: nitrogen dioxide

NH₃: ammonia

H₂O: water

N₂: nitrogen

By referring to the molar mass of each element of this reaction, one obtains the following proportions:



Reduction of nitrogen dioxide by AdBlue® (Diesel Exhaust Fluid):



NO₂: nitrogen dioxide

(NH₂)₂CO: AdBlue® (Diesel Exhaust Fluid)


O₂: oxygen

CO₂: carbon dioxide

N₂: nitrogen

H₂O: water

By referring to the molar mass of each element of this reaction, one obtains the following proportions:



ASSOCIATION ADILCA www.adilca.com * * *